




Pin Header Height:
B=6.5mm
B=6.7mm



TPYE 1



TPYE 2

SPECIFICATIONS

Current Rating:3Amps
Insulation Resistance:1000MΩ min
Withstanding Voltage: 1000VAC
Contact Resistance:20mΩ max
Operating Temperature:-40° C to+105° C
Standard:PBT
Contact Material:Brass
Contact Plating:Au or Sn Over Ni
Max. Processing Temp:200°C for 30-60second
(220°C for 10second)

- (1) Pin Spacing: 2.54±0.15mm
- (2) Product Name: FH-Female Header
- (3) No. of Rows: 1-Single 2-Dual Row
- (4) No. of Pins Per Row: 1-40
- (5) Insulator Material Height: 50=5.0mm; 85=8.5mm
- (6) Insulator Material wide: 25=2.5mm; 50=5.0mm
- (7) Contact Type: S-Straight; R-Right/Angle; W-SMT
- (8) Contact Material
Length: 20=2.8mm; 30=3.0mm; 32=3.2mm
- (9) Contact Plating: SN-Tin; XX=12Y, 14Y, 18Y, 20Y, 25Y, 30Y, 35Y; SD-Gold Flash/Tin
- (10) Insulator Material Option:
A=BK-PBT; B=BK-PA6T; C=BK-PA46; D=BK-LCP; S=Special