



Flange Height:  
B=0.8mm  
B=5.7mm



**TPYE 1**



**TPYE 2**

**SPECIFICATIONS**

Current Rating:3Amps  
Insulation Resistance:1000MΩ min  
Withstanding Voltage: 1000VAC  
Contact Resistance:20mΩ max  
Operating Temperature:-40° C to+105° C  
Standard:PBT  
Contact Material:Brass  
Contact Plating:As or Sn Over Ni  
Max. Processing Temp:200°Cfor30-60second  
(220°Cfor10second)

- (1) Pin Spacing: 254=2.54mm
- (2) Product Name:PH=Female Header
- (3) No. of Rows:1=Single 2=Dual Row
- (4) No. of Pins Per Row:1-40
- (5) Insulator Material Height:50=5.0mm;85=8.5mm
- (6) Insulator Material wide: 25=2.5mm;50=5.0mm
- (7) ContactType:S=Straight;R=Right/Angle;M=SMT
- (8) Contact Material  
Length:28=2.8mm;30=3.0mm;32=3.2mm
- (9) ContactPlating:SN=Tin;XXY=12Y, 14Y, 18Y, 20Y, 25Y, 30Y, 35Y;SD=Gold Flash/Tin
- (10) Insulator Material Option:  
A=BK-PBT;B=BK-PA6T;C=BK-PA46;D=BK-LCP;S=Special