



PIN ASSIGNMENT

P1 OBD M 16P MALE	P2 2.0 2*8 16P HOUSING
1	1
2	2
3	3
4	4
5	5
6	6
7	7
8	8
9	9
10	10
11	11
12	12
13	13
14	14
15	15
16	16

包装方式:卡好壳子+2PCS螺丝,用汽泡袋包装,用胶布封紧

测试要求:

1. 100%测试OK: 不能有短路。错位。断线。绝缘不良
2. 导通阻抗: 5 OHM
3. 绝缘阻抗: 5M OHM
4. 高压: 300V DC

注意:两头成型对裁后

脱皮留皮: 5mm, 脱芯: 2mm.

BILL OF MATERIAL

NO.	SPECIFICATION	Q'TY	ONSU	P/N.
⑥				
⑤		1PCS		
④	黑色外壳 (CC204)表面喷橡胶油 尾部封闭 侧面圆孔+螺丝	MM		
③	白色 2.0 2*8 16P HOUSING+2.0 端子 磷铜	1SET		
②	CABLE:OD=6.8 16C 26AWG BLACK	15G		
①	OBD 不短路PCB板+3号针(圆头)*16PCS 磷铜 OVERMOLD:25P PVC	1SET		

QUALITY SYMBOLS	GENERAL TOLERANCES		Customer number:	TITLE: OBD手柄	
	X.	±---			PART NO.
.X	±---				
.XX	±1.27				
.XXX	±0.51				
ANGLE TOLERANCES					
X°	±1.0°				
.X°	±---		APPROVED BY	DATE	
.XX°	±---				
.XXX°	---				
			SIZE: A4	SCALE: 1:1	UNIT: mm
THIRD ANGLE PROJECTION					