

模具编号		NO		MOULD NO		REMARK	
		1				THE FIRIST RELEASE	



P1 OBDII F
脱皮脱芯: 27/2MM
模具编号: 410A/B

PIN ASSIGNMENT

P1 OBDII F	P2 OBDII M
1	1
2	2
3	3
4	4
5	5
6	6
7	7
8	8
9	9
10	10
11	11
12	12
13	13
14	14
15	15
16	16

P2 OBDII M
脱皮脱芯: 40/4MM
模具编号: 408A/B

测试要求:

- 100%测试OK: 不能有短路。错位。断线。绝缘不良
- 导通阻抗: 5 OHM
- 绝缘阻抗: 5M OHM
- 高压: 300V DC

ROHS

3	CABLE:OD=6.8 16C+AL 26AWG 黑色	290	MM	
2	OBDII M (CC027)黑色无缺口+端子 磷铜 OVERMOLD: 45P PVC黑色	1	SET	纸箱: 46.5*31.5*32.5CM /A3B
1	OBDII F(CC033)黑色 磷铜针 OVERMOLD:45P PVC 黑色	1	SET	PE: 客供封口袋 长
ITEM	BILL OF MATERIAL /SPECIFICATION	QTY	UNIT	包装材料清单

QUALITY SYMBOLS		CUSTOMER NO.	
▽	GENERAL TOLERANCES	PRODUCT NAME	
	X. ±0.05	OBDIIM-OBDIIF (0.15MM)	
	.XX ±0.27	UNIT: MM SHEET: 1/1	
	.XXX ±0.51	PART NO.	
▽	ANGLE TOLERANCES	SIZE: A4 SCALE:1:1 REV: A/0	
	X° ±10°	THIRD ANGLE PROJECTION	
	.X° ±0.05	DRAWNBY	
	.XXX° ±0.05	APPROVEDBY	