


REV	CONTENT	CHK	DATE
V0.0	CONTENT	SK	2014-12-08

NOTES:

1. Rating:300V 15A;
2. Insulation Withstands Voltage: AC2000V/MIN
3. Insulation Resistance: 500MΩ or more at DC500V
4. Using Temperature Range: -40°C~+105°C
5. Screw Torque Vlaue:0.4Nm
6. Suitable Electric Wire: 28~12AWG
7. "★" is the important dimension.



SECTION:A-A

Total Pitch Tolerances in mm										Nominal dimension range in mm									
over	over	over	over	over	over	over	over	over	over	over	over	over	over	over	over	over	over	over	over
0	30	53	70	90	115	150	250	350	0	70	90	115	150	200	250	0	100	150	0
to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	to
30	53	70	90	115	150	250	350	0	30	53	70	90	115	150	200	250	320	100	150
±0.18	±0.20	±0.25	±0.3	±0.35	±0.44	±0.60	±0.70	±0.85	±0.20	±0.25	±0.30	±0.35	±0.44	±0.55	±0.70	±0.80	±0.90	±0.2	±0.3

ITEM	NAME OF PART	NO. OF PART	Q'TY	MATERIAL	NOTE
DWG	SK	DATE	2014-12-08	SIZE	A4 UNITS mm SHEET/OF 1/1
CHK	DATE			SCALE	2.5:1 7.62
APP.	DATE			NAME	
				DWGNO.	