



NOTES:

1. Rating: 300V 12A;
2. Insulation Withstands Voltage: AC2000V/MIN
3. Insulation Resistance:
500M Ω or more at DC500V
4. Using Temperature Range: -40°C/+105°C
5. Screw Torque Value: 0.4N.m
6. Suitable Electric Wire: 14-26AWG
- 7, " \star " the important dimension.

Total Pitch Tolerances in mm										Nominal dimension range in mm															
over	over	over	over	over	over	over	over	over	over	over	over	over	over	over	over	over	over	over	over	±	=	over	over	±	//
0	30	53	70	90	115	150	200	250	320	0	30	53	70	90	115	150	200	250	320	0	over	0	100	0	150
to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	to	to
30	53	70	90	115	150	200	250	320	to	30	53	70	90	115	150	200	250	320	10	10	all	100	100	100	150
±0.18	±0.20	±0.25	±0.3	±0.35	±0.44	±0.55	±0.70	±0.75	±0.20	±0.25	±0.30	±0.35	±0.44	±0.55	±0.70	±0.80	±0.90	0.2	0.3	0.3	0.3	0.2	0.3	0.5	

4	SOLDER PIN		P	BRASS	Tin Plated
3	BLOCK		P	BRASS	Ni Plated
2	SCREW		P	STEEL	M2.5/Zn Plated
1	HOUSING		/	PA66(V0)	02/03P
ITEM	NAME OF PART	NO. OF PART	Q"TY	MATERIAL	NOTE
DWG.	DATE	2020.08.28	UNITS	mm	SHEET/OF
CHK.	DATE		SCALE	3:1	A4
APP.	DATE		NAME	RF127 - X PIN	
			DWGNO.		

