



Number	Dimensions			Max. conductor resistance DC 20°C Ω/m
	TP(mm)	W(mm)	Tolerance	
06	6.35	7.62	±0.30	∅0.08 0.597
08	8.89	10.16	±0.30	
10	11.43	12.70	±0.30	
12	13.97	15.24	±0.30	
14	16.51	17.78	±0.30	
16	19.05	20.32	±0.30	
20	24.13	25.40	±0.30	
24	29.21	30.48	±0.30	
26	31.75	33.02	±0.30	
30	36.83	38.10	±0.30	
34	41.91	43.1	±0.40	
40	49.53	50.80	±0.40	
50	62.23	63.50	±0.40	
60	74.93	76.20	±0.40	
64	80.01	81.28	±0.40	

ORDER INFORMATION

S N F C 2 6 5 1 - 1 . 2 7 - G X X X - X

NOTES:

- Insulation material: PVC
Color: Gray
- SPECIFICATION
 - Rating: 300V
 - Conductor Size: 32AWG
 - Insulation resistance: 100MΩ/km min.
 - Operating temperature: -20°C~70°C.
- APPLICATION
 - Internal wiring of computers, electronic exchanges, measurement control devices, business machines, communication devices, and other electronic equipment.

30.5 Length=30.5m reel
76.5 Length=76.5m reel

No. of Positions: 06=6 Pins
64=64 Pins

R: Red print
F: flower print

32: 32AWG

ITEM	NAME OF PART	NO. OF PART	Q'TY	MATERIAL	NOTE
DWG	SK	DATE	SIZE	A4	UNITS 1/1
CHK		DATE	UNITS	MM	SCALE
APP		DATE			
					GF2651-0.08mm