



Number	Dimensions			Max. conductor resistance DC 20°C Ω/m
	TP(mm)	W(mm)	Tolerance	
06	6.35	7.62	±0.30	ø0.08 0.597
08	8.89	10.16	±0.30	
10	11.43	12.70	±0.30	
12	13.97	15.24	±0.30	
14	16.51	17.78	±0.30	
16	19.05	20.32	±0.30	
20	24.13	25.40	±0.30	
24	29.21	30.48	±0.30	
26	31.75	33.02	±0.30	
30	36.83	38.10	±0.30	
34	41.91	43.1	±0.40	
40	49.53	50.80	±0.40	
50	62.23	63.50	±0.40	
60	74.93	76.20	±0.40	
64	80.01	81.28	±0.40	

S N F C 2 6 5 1 - 1 . 2 7 - G X X X - X

1. Insulation material: PVC
Color: Gray
2. SPECIFICATION
 - . Rating: 300V
 - . Conductor Size: 32AWG
 - . Insulation resistance: 100MΩ/km min.
 - . Operating temperature: -20°C~70°C.
3. APPLICATION
 - . Internal wiring of computers, electronic exchanges, measurement control devices, business machines, communication devices, and other electronic equipment.

—30.5Length=30.5mlreel
76.5Length=76.5mlreel

— No. of Positions: 06 = 6 Pins
64 = 64 Pins

- R: Red print
- F: flower print
- 32: 32AWG

ITEM	NAME OF PART		NO. OF PART	Q'TY	MATERIAL		NOTE	
DWG	SK	DATE		SIZE	A4		UNITS	1/1
CHK		DATE		UNITS	MM		SCALE	 
APP		DATE						

GF2651-0.08mm